

## PRECAUTIONS

- Always use fresh, cement and sharp clean, well-graded aggregates.
- It is used with OPC/PPC grade of cement.
- Keep mixing time to a minimum – see above recommendations
- Always add cement into latex and not latex in cement.
- Do not apply coating over loose and debond surface
- Don't use hard water for mixing with polymer / cement.

## APPLICATION PROPERTIES

Pot Life (1.0 : 1.5)	35 - 45 minutes
Permeability to water (IS 2645 -1975)	Passes
Adhesion	Excellent

## PACKING

1, 5, 26, 50 & 100 Kg.

## HEALTH & SAFETY

Keep out of reach of children. Keep in cool place. If in contact with eyes, rinse with plenty of water and seek medical attention if irritation develops. If in contact with wash immediately with plenty of soap & water

## SHELF LIFE

12 Months

## STORAGE

Store between temp of +5 and 40 deg C. Keep containers closed when not in use. Protect from Direct Sunlight and freezing


**DISCLAIMER:** These suggestions and data are based on information, which we believe to be reliable. They are given for information only and in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

Recommended use in construction segment.



### apcotex industries limited

49-53, 3rd Floor, Mahavir Centre, Plot No. 77, Sector-17,  
Vashi, Navi Mumbai-400703 Maharashtra, India  
Tel.:91-22-2777-0800 Fax :91-22-2741-2052  
Email : apcobuild@apcotex.com Website : www.apcobuild.co.in



# ApcoBuild™

Build Smarter

## APCOGUARD S™

### SPECIALTY SBR LATEX FOR REPAIRS & WATERPROOFING

- Provides excellent water impermeability
- Offers good workability at reduced water/ cement ratio
- Excellent Bonding between old and new substrate
- Acts as a protective coat for steel rebar
- Useful for improving Flexural, Tensile and Bond strength and for water proofing of concrete/mortar
- Improved toughness and flexibility
- Mixes can be applied in thinner sections
- Improves abrasion resistance of flooring